

SM6S -H Series


SURFACE MOUNT AUTOMOTIVE TRANSIENT VOLTAGE SUPPRESSORS

VOLTAGE RANGE: 10- 36V
POWER: 4600Watts



DO-218AB





Features

- Ideally suited for load dump protection
- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- AEC-Q101 qualified
- Junction passivation optimized design technology
- T_J =175 °C capability suitable for high reliability and automotive requirement
- Moisture sensitivity level: level 1, per J-STD-020
- Compliant to RoHS directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- High temperature stability due to unique oxide passivation and patented PAR®construction
- Integrally molded heatsink provides a very low thermal resistance for maximum heat dissipation
- High temperature soldering guaranteed: 260°C for 10 seconds at terminals
- Low forward voltage drop

APPLICATIONS

Use in sensitive electronics protection against voltage transients induced by inductive load switching and lighting, especially for automotive load dump protection application.


Mechanical Data

- Case: DO-218AB integrally mounted in the encapsulation
- Terminals: Plated, solderable per MIL-STD-750, Method 2026
- Polarity: Heatsink is anode
- Mounting Position: Any
- Weight: 2.691g (approximately)

RoHS compliant



Bi-directional



Uni-direction

Maximum Ratings and Thermal Characteristics (T_C = 25°C unless otherwise noted)

Characteristic	Symbol	Value	Unit
Peak pulse power dissipation with 10/1000µs waveform 10/10,000µs waveform	P_{PPM}	4600 3600	W
Steady state power dissipation	P_D	6.0	W
Peak pulse current with a 10/1000µs waveform (NOTE 1)	I_{PPM}	See Table 1	A
Peak forward surge current, 8.3ms single half sine-wave	I_{FSM}	600	A
Typical thermal resistance junction to case	$R_{\Theta JC}$	0.95	°C/W
Operating junction and storage temperature range	T_J, T_{STG}	–55 to +175	°C

Notes: (1) Non-repetitive current pulse derated above T_A=25°C


ELECTRICAL SPECIFICATIONS (T_A = 25°C unless otherwise noted)

Type	Breakdown Voltage $V_{(BR)}$ (V)		Test Current I_T	Stand-off Voltage V_{WM}	Maximum Reverse Leakage at V_{WM} I_D	Maximum Reverse Leakage at V_{WM} Tc=175°C	Max. Peak Pulse Current at 10/1000μs Waveform	Maximum Clamping Voltage at I_{PPM} V_C
	Min.	Max.	(mA)	(V)	(μA)	I_D(μA)	(A)	(V)
SM6S10CA-H	11.1	13.6	5.0	10.0	15	250	245	18.8
SM6S10A-H	11.1	12.3	5.0	10.0	15	250	271	17.0
SM6S11CA-H	12.2	14.9	5.0	11.0	10	150	229	20.1
SM6S11A-H	12.2	13.5	5.0	11.0	10	150	253	18.2
SM6S12CA-H	13.3	16.3	5.0	12.0	10	150	209	22.0
SM6S12A-H	13.3	14.7	5.0	12.0	10	150	231	19.9
SM6S13CA-H	14.4	17.6	5.0	13.0	10	150	193	23.8
SM6S13A-H	14.4	15.9	5.0	13.0	10	150	214	21.5
SM6S14CA-H	15.6	19.1	5.0	14.0	10	150	178	25.8
SM6S14A-H	15.6	17.2	5.0	14.0	10	150	198	23.2
SM6S15CA-H	16.7	20.4	5.0	15.0	10	150	171	26.9
SM6S15A-H	16.7	18.5	5.0	15.0	10	150	189	24.4
SM6S16CA-H	17.8	21.8	5.0	16.0	10	150	160	28.8
SM6S16A-H	17.8	19.7	5.0	16.0	10	150	177	26.0
SM6S17CA-H	18.9	23.1	5.0	17.0	10	150	151	30.5
SM6S17A-H	18.9	20.9	5.0	17.0	10	150	167	27.6
SM6S18CA-H	20.0	24.4	5.0	18.0	10	150	143	32.2
SM6S18A-H	20.0	22.1	5.0	18.0	10	150	158	29.2
SM6S20CA-H	22.2	27.1	5.0	20.0	10	150	128	35.8
SM6S20A-H	22.2	24.5	5.0	20.0	10	150	142	32.4
SM6S22CA-H	24.4	29.8	5.0	22.0	10	150	117	39.4
SM6S22A-H	24.4	26.9	5.0	22.0	10	150	130	35.5
SM6S24CA-H	26.7	32.6	5.0	24.0	10	150	107	43.0
SM6S24A-H	26.7	29.5	5.0	24.0	10	150	118	38.9
SM6S26CA-H	28.9	35.3	5.0	26.0	10	150	99	46.6
SM6S26A-H	28.9	31.9	5.0	26.0	10	150	109	42.1
SM6S28CA-H	31.1	38.0	5.0	28.0	10	150	92	50.1
SM6S28A-H	31.1	34.4	5.0	28.0	10	150	101	45.4
SM6S30CA-H	33.3	40.7	5.0	30.0	10	150	86	53.5
SM6S30A-H	33.3	36.8	5.0	30.0	10	150	95	48.4
SM6S33CA-H	36.7	44.9	5.0	33.0	10	150	78	59.0
SM6S33A-H	36.7	40.6	5.0	33.0	10	150	86	53.3
SM6S36CA-H	40.0	48.9	5.0	36.0	10	150	72	64.3
SM6S36A-H	40.0	44.2	5.0	36.0	10	150	79	58.1


Note: For all types maximum V_F = 1.9V at I_F = 100A measured on 8.3ms single half sine-wave or equivalent square wave, duty cycle = 4 pulses per minute maximum

CHARACTERISTICS CURVES (T_A = 25°C unless otherwise noted)


Power Derating Curve




Load Dump Power Characteristics (10ms Exponential Waveform)




Pulse Waveform



Reverse Power Capability




Part Numbering System





Soldering Parameters


Feflow Condition		Lead-free assembly
Pre Heat	- Temperature Min ($T_{s(min)}$)	150°C
	- Temperature Max ($T_{s(min)}$)	200°C
	- Time (min to max) (t_s)	60-180 secs
Average ramp up rate (Liquidus Temp (T_L) to peak		3°C/second max
$T_{S(max)}$ to T_L - Ramp-up Rate		3°C/second max
Reflow	- Temperature (T_L) (Liquidus)	217°C
	- Time (min to max) (t_s)	60-150 seconds
Peak Temperature (T_P)		$260^{+0/-5}$ °C
Time within 5°C of actual peak Temperature (t_p)		20-40 seconds
Ramp-down Rate		6°C/second max
Time 25°C to peak Temperature (T_P)		8 minutes Max.
Do not exceed		280°C



Surface Mount Tape and Reel Packaging







Ref.	Dimensions	
	Millimeters	Inches
A0	10.80 ± 0.3	0.425± 0.012
B0	16.13 ± 0.3	0.635 ± 0.012
C	330.0 ± 0.3	13.0 ± 0.012
D0	1.55 ± 0.2	0.061 ± 0.008
D1	1.55 ± 0.2	0.061± 0.008
E	1.75 ± 0.2	0.069 ± 0.008
E1	13.30 ± 0.2	0.524 ± 0.008
F	11.50 ± 0.2	0.453 ± 0.008
P0	4.00 ± 0.2	0.157 ± 0.008
P1	16.00 ± 0.2	0.630 ± 0.008
P2	2.00 ± 0.2	0.079 ± 0.008
W	24.00 ± 0.2	0.945 ± 0.008
W1	25.85 ± 0.2	1.018 ± 0.008

ORDERING INFORMATION

PART No.	UNIT WEIGHT (g)typ	REEL (PCS)	PER CARTON (PCS)	DESCRIPTION
SM8SxxA	2.985	750	3000	13 inch reel pack

Notice

- Reproducing and modifying information of the document is prohibited without permission from SUNMATE electronics.
- SUNMATE electronics reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- SUNMATE electronics or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies including damages incidentally and consequentially occurred.
- No license, express or implied, to any intellectual property rights is granted by this document, SUNMATE electronics assumes no liability whatsoever, and disclaims any express or implied warranty,relating to sale and/or use of SUNMATE products including warranties of fitness for particular purpose and merchantability or infringement of any patent, copyright, or other intellectual property right.
- Purchasers are solely responsible for the choice, selection, and use of sunmate products and sunmate assumes no liability for application assistance or the design of Purchasers' products. Information contained herein is intended to provide a product description only.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fullyindemnify SUNMATE electronics for any damages resulting from such improper use or sale.
- This document is the 3.3rd version which is made in 7-Nov.-2020.

This document supersedes and replaces all information previously supplied.

LOGO(SUNMATE) is a registered trademark of SUNMATE Electronics Co.,Ltd.