GBU15A-GBU15M


GLASS PASSIVATED SINGLE-PHASE BRIDGE RECTIFIER

VOLTAGE RANGE: 50 - 1000V
CURRENT: 15.0A



Features

- High Reliability
- High Current Capability
- Low Forward Voltage Drop
- Glass Passivated Die Construction
- High Surge Current Capability
- Ideal for Printed Circuit Boards



Mechanical Data

- Case: Molded Plastic
- Terminals: Plated Leads Solderable per MIL-STD-202, Method 208
- Polarity: As Marked on Body
- Weight: 4.0 grams (approx.)
- Mounting Position: Any
- Marking: Type Number

RoHS COMPLIANT

Maximum Ratings and Electrical Characteristics T_A = 25°C unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Characteristic	Symbol	GBU15A	GBU15B	GBU15D	GBU15G	GBU15J	GBU15K	GBU15M	Unit
Maximum recurrent peak reverse voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum average forward Tc=100℃ output current	$I_{F(AV)}$	15.0							A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load	I_{FSM}	240.0							A
Maximum instantaneous forward voltage at 7.5 A	V_F	1.0							V
Maximum reverse current @T_A=25℃	I_R	5.0							μA
at rated DC blocking voltage @T_A=125℃		500.0							mA
Typical junction capacitance per leg (note 3)	C_J	211				94			pF
Typical thermal resistance per leg (note 2)	$R_{\theta JA}$	21.0							℃/W
(note 1)	$R_{\theta JC}$	2.2							
Operating junction temperature range	T_J	- 55 ---- + 150							℃
Storage temperature range	T_{STG}	- 55 ---- + 150							℃

NOTE: 1. Unit case mounted on 3.2x3.2x0.12" thick (6.2x8.2x0.3cm) Al. Plate.
2. Units mounted in free air, no heat sink on P.C.B., 0.5x0.5"(12x12mm) copper pads, 0.375"(9.5mm) lead length.
3. Measured at 1.0 MHz and applied reverse voltage of 4.0 volts.

FIG.1 -- DERATING CURVE FOR OUTPUT RRECTIFIED CURRENT




FIG.2 -- TYPICAL FORWARD CHARACTERISTIC




FIG.3 -- MAXIMUM NON-REPETITIVE PEAK FORWARD DURGE CURRENT




FIG.4 -- TYPICAL REVERSE CHARACTERISTIC




FIG.5 -- TYPICAL JUNCTION CAPACITANCE PER LEG




FIG.6 -- TYPICAL TRANSIENT THERMAL IMPEDANCE

